


DIN Rail Enclosure—Medium

For Use with GreenMAX® DRC Room Control System and Other DIN Rail Components



Description

DIN Rail Enclosures are agency-listed cabinets designed to accept any equipment installable to ANSI-standard DIN rail. This allows highly flexible installations which can be custom tailored to your specific application without the need for expensive custom cabinetry. The Enclosures consist of a back cabinet with DIN rails and wiring space, a dead front that hides the wiring, and a locking cover. The dead front is specifically engineered to allow separation of powered wiring from the user, allowing the user to see the status of all installed equipment and operating test/bypass switches without being exposed to line voltage wiring and requiring Personal Protective Equipment (PPE). The locking door is provided to secure the panel. Leviton DIN Rail Enclosures are well suited for the GreenMAX® DRC Room Control System and can be provided either as empty enclosures for field installation of equipment or as factory pre-configured* enclosures with pre-installed modules and/or wiring for easy installation. DIN rail spacers are used to fill blank spaces between modules to ensure no gaps in the openings of the dead front cover. There are 4 sizes to choose from that can be combined in any configuration, as needed. All spacers are finished to match the medium and large size DINRK series DIN rail cabinets.


Applications

- GreenMAX DRC Room Control Systems
- Third party ANSI-standard DIN rail installations
- DIN rail meters such as the VerifEye™ Series 4000 and 4100

Features

- Available in small, medium and large formats
- Medium contains 3 rails (15"/38cm each)
- Medium is 25"x21"x4" (64cm x 54cm x 11cm)
- Can accommodate GreenMAX DRC components or any other DIN rail mount load control or other 3rd party control equipment that is ANSI-standard
- Optionally pre-configured for easy installation and ensured compatibility - see page 4 for ordering details
- ETL and UL listed to UL and CSA Standards as an Industrial Controls Equipment Enclosure
- CE listed

Installation Instructions



Areas marked as “(A)/(B)” are intended to be used as wire-ways. It is recommended that one side be designated for power and lighting wiring plus any other Class 1 wiring. The other side for Class 2, lower voltage wiring.

Organize any devices installed so that the wiring types to these devices can be kept separated per the “(A)/(B)” scheme identified above.

Perforated metal dividers are provided so tie wraps, or other fastening devices, can be used to secure wires and ensure 1/4-inch separation between high and low voltages.


Conduit can access cabinet through the top, bottom, or sides. However, conduit access shall be located so that higher voltage wiring (Class 1 - power and lighting) and lower voltage wiring (Class 2 - control) can be kept separated per the “(A)/(B)” scheme identified above.

Cabinet can be used with or without the dead front panel installed

- When used with the dead front panel, the dead front panel must be secured with grounding screws provided
- When the dead front panel is properly secured, the front door can be open when power is energized
- When used without the dead front panel, the provided grounding kit (DINRK-GWI) must be installed that provides ground to the front door

All unused openings in dead front panel must be filled with DINFL-xxx series fillers.

Dimensions



Specifications

Electrical	
Cabinet Dimensions	25" x 21" x 4" (64cm x 54cm x 11cm)
DIN Rail Quality	3
DIN Rail Length	13.7" (35cm)
Environmental	
Operating Temperature	32° to 122° F (0° to 50° C)
Storage Temperature	-4° to 185° F (-20° to 85° C)
Relative Humidity	0-90% non-condensing
Other	
Listings	ETL, cETL, CE, UL and RCM listed, IP10 Rated for no water ingress protection
Warranty	5-Year Limited Warranty
Color	White

Ordering Information

DIN Rail Rack Mount Enclosure - Medium	
Cat. No.	Description
DINRK-A03	DIN Rail Rack Mount Enclosure, Medium, 21" x 25" with (3) 13.7" (35cm) rails
DINRK-A03-CFG	Configured Panel, Requires ASAP or Factory Design - DIN Rail Rack Mount Enclosure, (1) " (cm) rail
DINFL-S1W	1 DIN unit wide spacer 0.67" in (17mm)
DINFL-S2W	2 DIN units wide spacer 1.34" (34mm)
DINFL-FMW	½ rail width filler for Medium cabinet. Use 2 units to fill an entire rail 6.78" (172mm)
DINFL-FLW	½ rail width filler for Large cabinet. Use 2 units to fill an entire rail 9.54" (242mm)

Leviton Manufacturing Co., Inc. Lighting & Controls

10385 SW Avery Street, Tualatin, OR 97062 **tel** 800-736-6682 **tech line** (6:00AM-4:00PM PT Mon-Fri) 800-959-6004

Leviton Manufacturing Co., Inc. Global Headquarters

201 North Service Road, Melville, NY 11747-3138 **tel** 800-323-8920 **tech line** (8:00AM-10:00PM ET Mon-Fri, 9:00AM-7:00PM ET Sat, 9:00AM-5:00PM ET Sun) 800-824-3005

Visit our Website at: www.leviton.com

©2026 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.